

Resource Production Equipment Subject: General Rules

### **Summary**

This section contains the formulas, rules, and principles, and the rate schedules and calculation procedures for determining the assessed value of oil and gas well resource production equipment, and buildings located at an oil or gas well site.

## **Description**

Resource production equipment includes the fixtures, machinery and other appliances by which petroleum oil or gas is produced to the surface, stored, transported from a well site or a battery or gas handling site, or is compressed.

Resource production equipment does not include the fixtures, machinery and other appliances by which petroleum oil or gas is stored at a battery site, or is compressed where the gas is, for the most part, a by-product of petroleum oil production.

## Oil or Gas Well Site

The area of land on or under which is located the resource production equipment used to raise or pump the oil or gas to the surface, the resource production equipment used to inject air, water, steam or gas to enhance the production of a well, resource production equipment used to test or collect well productivity where wells and testing/collection equipment are connected on the same parcel of land, or the resource production equipment at a water source well, that was operated for 30 or more days in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

The resource production equipment located at an oil well site includes the pumping equipment, wellhead assembly, tubing and rods, flow lines, manifolds and well accessories.

The resource production equipment located at a gas well site includes the wellhead assembly, tubing, chemical equipment, water handling equipment, metering equipment, flow line and manifold.

The resource production equipment located at an oil or gas multi-well pad site includes the equipment for an oil or gas well site along with production testing or collection equipment (meters, separators, manifold, flow line, etc.).

The resource production equipment used to inject air, polymer, water, steam or gas to enhance the production of a well, and the resource production equipment at a water source well, includes the pumping equipment, wellhead assembly, tubing and rods, metering equipment, control valves, flow lines, manifolds, cable and well accessories.

#### New Well Site

An oil or gas well site that was drilled in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

### Swabber Well Site

An oil or gas well site where on July 1 of the preceding year to which the assessment roll relates, the resource production equipment used in the preceding year has been removed from the site, with the exception of the wellhead, and has not been replaced with any other on-site resource production equipment.

#### Shut-In Single Well Site

The area of land on or under which is located the resource production equipment used to raise or pump the oil or gas to the surface, the resource production equipment used to inject air, water, steam or gas to enhance the production of a well, or the resource production equipment at a water source well, that was operated for less than 30 days in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

Date: 25/07/23 Page: 1



Resource Production Equipment Subject: General Rules

## Shut-In Multi-Well Pad Site

The area of land on or under which is located resource production equipment used to raise or pump the oil or gas to the surface and resource production equipment used to test or collect well productivity where wells and testing/collection equipment are connected on the same legal subdivision (LSD) of the same legal land description. All resource production equipment, both for production and testing/collection, have operated for less than 30 days in the 12 month period ending July 1 of the preceding year to which the assessment roll relates.

#### Observation Well Site

The area of land on or under which is located the resource production equipment used to monitor an oil or gas well to enhance the production of the well.

## Gas Storage Well Site

The area of land on or under which is located the resource production equipment used to inject gas into a gas cavern or sub surface formation and to pump gas from a gas cavern or subsurface formation.

### Flow Line

A flow line is resource production equipment consisting of a line of pipe used to transport oil or gas within a well site to a battery or gas handling site.

#### Replacement Cost New

The replacement cost new of oil and gas well resource production equipment and buildings located at an oil or gas well site, or a new well site shall be determined by the standard unit method.

For the purposes of identifying the presence and classification of oil and gas well resource production equipment so as to determine its replacement cost new using the standard unit method, the assessor shall use and rely upon information reported by the Saskatchewan Ministry of the Economy and/or its Minister (or any successor of either) in the administration of *The Oil and Gas Conservation Act* and corresponding regulation (or any successor legislation), to the extent such information is available.

The replacement cost new of oil and gas well resource production equipment located at a swabber well site or shut-in single well site or shut-in multi-well pad site or observation well site shall be limited to the wellhead assembly which shall be determined in accordance with the wellhead assembly specifications in Chapter 4 - Resource Production Equipment, Section 4.1.3 - Oil and Gas Well Resource Production Equipment, Well Classification

The replacement cost new of oil and gas well resource production equipment located at an observation well site or gas storage well site, and the replacement cost new of flow lines shall be determined by the unit-in-place method.

The trended original cost method for determining replacement cost new shall be used where the replacement cost new of specific oil or gas well resource production equipment cannot be determined by the standard unit method or the unit-in-place method.

The trended original cost shall include all direct and indirect costs. Direct costs include materials, labour, supervision, equipment rentals, and utilities. Indirect costs include architectural and engineering fees, building permits, title and legal fees, insurance, interest and fees on construction loans, taxes incurred during construction, advertising and sales expenses, and overhead and profit. Trended original costs shall be determined free on board (FOB) the oil or gas well site as of January 1, 2023.

### Standard Unit Method

The replacement cost new shall be determined as follows:

- 1. Determine the classification of the well.
- 2. Determine the resource production equipment needed to operate a substitute well. The substitute well must perform the same function as the well being valued.



Resource Production Equipment Subject: General Rules

3. Calculate the replacement cost new of the resource production equipment located at the well by summing the replacement cost of the substitute resource production equipment.

### **Unit-In-Place Method**

The replacement cost new shall be determined as follows:

- 1. Determine the type of resource production equipment using the rating guide.
- 2. Determine the features requiring a unit-in-place lump sum or percentage adjustment.
- 3. Calculate the replacement cost new of the resource production equipment by adjustment of the base rate by the unit-in-place adjustments.

### Trended Original Cost Method

The replacement cost new shall be determined as follows:

- 1. Determine the original construction cost of all the resource production equipment at the facility.
- 2. Determine the direct and indirect costs requiring an adjustment.
- 3. Determine the direct and indirect cost factor for oil and gas resource production equipment required to adjust construction costs to January 1, 2023.
- 4. Calculate the construction cost of all the resource production equipment at the facility by adjusting the original construction cost for any direct or indirect costs requiring adjustment and multiplying the adjusted original construction cost by the comparative cost index.
- 5. Determine replacement cost of resource production equipment that can be separately identified and rated by the unit-in-place method.
- 6. Calculate the replacement cost of the resource production equipment that cannot be separately identified by subtracting the replacement cost of separately identified components from the construction cost of all the resource production equipment at the facility.

### **Physical Deterioration**

The amount of physical deterioration for oil and gas well resource production equipment, buildings and structures shall be determined using the lifetime depreciation method. No allowance shall be made for functional and economic obsolescence, except as may be accounted for in the downtime allowance or the production adjustment factor.

### Lifetime Depreciation Method

The amount of physical deterioration shall be 40 percent. When calculating replacement cost new less depreciation no additional allowance shall be made for physical deterioration except as may be accounted for in the production adjustment factor.

#### **Downtime Allowance**

The downtime allowance for oil and gas well resource production equipment shall be determined by the schedule of rates method.

The downtime allowance shall account for the loss in value due to under-utilization of the resource production equipment. This includes any loss in value due to differences in replacement cost and differences in the amount of depreciation, that have not been taken into account using the procedures in this Manual.

#### Schedule of Rates Method

The downtime allowance shall be 10 percent. When calculating replacement cost new less depreciation and downtime, no additional allowance shall be made for downtime except as may be accounted for in the production adjustment factor.





Resource Production Equipment Subject: General Rules

## **Production Adjustment Factor**

The production adjustment factor for oil and gas well resource production equipment, buildings and structures located at an oil or gas well site, and flow lines shall be determined by the schedule of rates method.

The production adjustment factor shall account for the loss in value due to under-utilization of the resource production equipment, buildings and structures. This includes any loss in value due to differences in replacement cost and differences in the amount of depreciation, that have not been taken into account using the procedures in this Manual.

A production adjustment factor shall not be applied to the oil and gas well resource production equipment, buildings and structures located at a new well site, swabber well site, shut-in single well site, shut-in multi-well pad site, observation well site, or gas storage well site.

## Schedule of Rates Method

The production adjustment factor shall be 0.75 for qualified resource production equipment, buildings, structures and flow lines.



Resource Production Equipment Subject: General Rules

## **Qualifying Production Level**

The production adjustment factor shall be applied to resource production equipment, buildings, structures and flow lines located at an oil or gas well site. The factor shall be a three year average of production from a 36 month period ending July 1 of the preceding year to which the assessment roll relates.

The average production of the well shall be determined as follows:

- 1. Determine the volume of oil or gas produced by the well during the 12 month period of July 1 to June 30 for each of the three years.
- 2. Determine the number of days the well was operated during the 12 month period of July 1 to June 30 for each of the three years.
- 3. Calculate the production of the well for each year by dividing the volume of oil or gas produced by the well for the year by the number of days the well was operated during the year.
- 4. Calculate the average production of the well by summing the production of the well for the three years and dividing by three.

#### Oil Wells

		<b>Qualifying Production Level</b>		
Well Area (Abbreviation)	Crude Type	barrels/day	m³/day	
Working (WE)	Light	1.05	0.166	
Weyburn (WE)	Medium	1.09	0.173	
	Light	0.73	0.116	
Swift Current (SC)	Medium	1.43	0.228	
	Heavy	2.58	0.410	
V:1(VD)	Light	0.56	0.090	
Kindersley (KD)	Heavy	2.87	0.456	
North Battleford - South (NB-S)	Heavy	3.11	0.495	
North Battleford - North (NB-N)	Heavy	3.11	0.495	

### Gas Wells

Wall Area (Abbresistion)	Qualifying Production Level		
Well Area (Abbreviation)	cu.ft./day m³/da		
Weyburn (WE)	14,952	423.39	
Swift Current (SC)	11,562	327.40	
Kindersley (KD)	13,096	370.85	
North Battleford - South (NB-S)	14,952	423.39	
North Battleford - North (NB-N)	14,952	423.39	



Resource Production Equipment Subject: General Rules

## **Calculation Procedure**

## Resource Production Equipment at an Oil or Gas Well Site

Description	Document No.	Page No.
Standard Unit Resource Production Equipment [a), b), c) ]		
a) Determine Well Characteristics		
a <sub>1</sub> . Well Area	4.1.3	1
a <sub>2</sub> . Well Type	4.1.3	1
a <sub>3</sub> . Crude Type	4.1.3	2
a <sub>4</sub> . Completion	4.1.3	2
a <sub>5</sub> . Depth	4.1.3	2
a <sub>6</sub> . Rated Volume	4.1.3	2
a <sub>7</sub> . Facility Type	4.1.3	2
a <sub>8</sub> . Days Operated	4.1.3	2
b) Determine Substitute Well Features	4.1.3	3-18
c) Base Rate = $(c_1 + c_2 + c_3 \dots + c_9)$		
c <sub>1</sub> . Pumping Equipment Rate	4.1.5	1-5
c <sub>2</sub> . Wellhead Assembly Rate	4.1.4	1
c <sub>3</sub> . Tubing and Rods Rate	4.1.7	1
c <sub>4</sub> . Chemical Equipment Rate	4.1.13	1
c <sub>5</sub> . Water Handling Equipment Rate		
$c_5 = (c_{5.1} + c_{5.2})$		
c <sub>5.1</sub> Separator Rate	4.1.8	1-2
c <sub>5.2</sub> Scraper Traps Rate	4.1.22	1
c <sub>6</sub> . Metering Equipment Rate	4.1.10	1-2
c7. Control Valves Rate	4.1.11	1-2
c <sub>8</sub> . Manifold Rate	4.1.21	1
c <sub>9</sub> . Flow Line Rectifier Rate	4.1.15	1
d) Unit-in-Place Resource Production Equipment	4.1.1	2
e) Trended Original Cost Resource Production Equipment	4.1.1	3
f) Replacement Cost New = $(c + d + e)$		
g) RCN less Physical Deterioration and Downtime		
Allowance = $f x (1 - (g_1 + g_2))$		
g <sub>1</sub> . Physical Deterioration	4.1.1	3
g <sub>2</sub> . Downtime Allowance	4.1.1	3
h) Production Adjustment Factor	4.1.1	3-5
i) Assessed Value = $(g x h)$		

The calculation procedure for oil and gas well buildings on an oil or gas well site is found on Document 3.1.3, Page 1.



Resource Production Equipment Subject: Comparative Cost Factor

### **Description**

The comparative cost factors are used to determine the replacement cost of oil and gas well resource production equipment valued by the trended original cost method.

## **Application**

The trended original cost method shall be used when the individual components of resource production equipment cannot be determined or estimated.

The trended original cost method shall not be used to determine the replacement cost of resource production and equipment located at an oil or gas well site, or to determine the replacement cost of resource production equipment that can be separately identified and rated.

### Comparative Cost Factor

The comparative cost factor shall be used to calculate the replacement cost new of resource production equipment as of January 1, 2023.

#### **Factors**

Year	Comparative Cost Factor
1940 and older	
1941	
1942	
1943	
1944	
1945	
1946	
1947	
1948	
1949	
1950	
1951	
1952	
1953	
1954	
1955	
1956	
1957	
1958	
1959	
1960	
1961	
1962	
1963	
1964	
1965	
1966	
1967	
1968	
1969	
1970	
1971	
1972	
1973	

Portions of this section are not available for viewing due to licensing with Marshall and Swift, published by CoreLogic Inc. Therefore the factors etc. have been intentionally left blank.

This information is available for purchase by contacting:

Technical Standards and Policy Division Saskatchewan Assessment Management Agency 200 – 2201 – 11<sup>th</sup> Avenue Regina, Saskatchewan S4P 0J8

Phone: (306) 924-8000 Toll Free: 1-800-667-SAMA (7262) Fax: (306) 924-8070

Email: info.request@sama.sk.ca

Website: <a href="http://www.sama.sk.ca">http://www.sama.sk.ca</a>



Resource Production Equipment Subject: Comparative Cost Factor

Year	Comparative Cost Factor
1974	
1975	
1976	
1977	
1978	
1979	
1980	
1981	
1982	
1983	
1984	
1985	
1986	
1987	
1988	
1989	
1990	
1991	
1992	
1993	
1994	
1995	
1996	
1997	
1998	
1999	
2000	
2001	
2002	
2003	
2004	
2005	
2006	
2007	
2008	
2009	
2010	
2011	
2012	
2013	
2014	
2015	
2016	
2017	
2018	
2019	
2020	
2021	
2022 and newer	

This table is a derivative work based on the "Marshall & Swift Valuation Service" which is the copyrighted material of Marshall & Swift, published by CoreLogic Inc. © 2022. Unauthorized reproduction is expressly prohibited.





Resource Production Equipment Subject: Well Classification

### **Well Characteristics**

This section describes the formulas, rules and procedures for determining the classification of resource production equipment located at an oil or gas well site. Oil and gas well resource production equipment shall be classified in accordance with the following well characteristics:

Well Area Depth

Well Type Rated Volume
Crude Type Facility Type
Completion Days Operated

## Well Area

The well areas shall be:

Well Area (Abbreviation)	Description	
Wayburn (WE)	All municipalities east of the third meridian, from	
Weyburn (WE)	R.M. 1 to R.M. 371 inclusive, except R.M. 282.	
Swift Current (SC)	All municipalities west of the third meridian, from	
Swiit Current (SC)	R.M. 43 to R.M. 261 inclusive.	
	All municipalities west of the third meridian, from	
Kindersley (KD)	R.M. 282 to R.M. 382 inclusive, including R.M.	
	372.	
North Dattleford South (ND S)	All municipalities from R.M. 394 to R.M. 555	
North Battleford - South (NB-S)	inclusive.	
North Dattleford North (ND N)	All municipalities from R.M. 561 to R.M. 622	
North Battleford - North (NB-N)	inclusive and the Northern Administrative District.	

### Well Type

The well types shall be:

Oil Polymer Injection
Oil (New) Gas Injection

Gas Continuous Steam Injection
Gas (New) Cyclic Steam Injection

Air Injection Water Source

Water Injection Water Source (New)

Oil (New) and Gas (New) wells are those wells located on a new well site that was drilled in the 12 month period ending July 1 of the year immediately preceding the year to which the assessment roll relates.



Resource Production Equipment Subject: Well Classification

## Crude Type

The crude types shall be:

Light Medium Heavy

### **Completion:**

The completion types shall be:

Vertical Horizontal

## Depth

The depth of an oil or gas well shall be determined by measuring the distance from the kelly bushing to the average depth of the perforations in the well casing, or in the case of a horizontal well, the distance from the kelly bushing to the kick off depth.

### Rated Volume

The volume for an oil well shall be determined based on the combined volume of oil and water produced.

The volume for a water source well shall be determined based on the volume of water produced.

The period July 1 to June 30 of the year immediately preceding the year to which the assessment roll relates, shall be used to determine the volume and days operated.

The rated volume shall be determined by application of the following formula:

 $RV = volume \div days operated$ 

where: RV = rated volume

volume = number of barrels of oil and/or water produced by the well

days operated = number of days the well was operated

## Facility Type

The facility types shall be:

Type	Description		
Tanks	Used to store oil on site until it is transferred to a battery.		
Flow Lines	Used to transfer oil directly to a battery or gas directly to a gas plant, satellite or compressor station.		

## **Days Operated**

The number of days that the well was operated during the period July 1 to June 30 of the year immediately preceding the year to which the assessment roll relates.

### Shut-In Reporting Period

The shut-in status for single well sites and multi-well pad sites shall be determined from the 12 month period ending July 1 of the year immediately preceding the year to which the assessment roll relates.

#### **Pumping Units**

All oil well pumping units shall be conventional or hydrabeam.





Resource Production Equipment Subject: Well Classification



Resource Production Equipment Subject: Well Classification

# Water Handling Equipment

Type	Description	Rate (\$)
1	<ul> <li>20% of meter cabinet</li> <li>10% - 125 - 260 psi 12"x5' vertical two phase separator</li> <li>60% - 2" receiving and launching trap without bypass</li> <li>70% - test leads</li> </ul>	13,670
2	<ul> <li>125 – 260 psi 24"x10' vertical two phase separator</li> <li>3" receiving and launching trap with bypass</li> </ul>	67,540

# **Metering Equipment**

Type	Description	Rate (\$)
	• One 300 psi gas, dry flow recorder chart 100" with 2 pens	
1	• 50% of one 3" 300 psi senior quick change	16,270
	• 50% of one 3" 300 psi simplex	

# Water Handling Buildings

Type	Description	Rate (\$)
1	<ul> <li>10% - 8' height, 64 sq.ft. metal shed with lining and insulation, floor and heat</li> <li>10% - 40 barrel open top plastic pop tank</li> <li>10% - 120 barrel open top plastic pop tank</li> </ul>	2,390
2	<ul> <li>8' height, 64 sq.ft. metal shed with lining and insulation, floor and heat</li> <li>300 barrel lap welded steel stock tank with open top</li> </ul>	59,210

# **Chemical Equipment**

Type	Description	Rate (\$)
1	Alcohol drip (9 imp. gal. tank)	2,020



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Weyburn Well Area - Light Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... 160 pumping unit

• All other vertical well pumping units:

Rated Volume	Depth (ft.)			
(barrels/day)	<3000	3000 to <4800	4800 to <5700	≥ 5700
< 3	40	114	114	228
3 to < 10	57	114	114	228
10 to < 75	57	160	160	320
75 to < 120	80	160	228	320
120 to < 200	PC-120	228	320	456
≥ 200	PC-120	320	456	640
Rated volume = oil per day + (water per day $\div$ 2)				

### 2. Horizontal Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 to < 200	228	
200 to < 300	456	
300 to < 450	456	
450 to < 600	640	
≥ 600	912	
Rated volume = oil per day + (water per day $\div$ 2)		

## 3. Prime Mover ... electric motor.

### Wellhead Assembly

Vertical ... threaded 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

## **Tubing and Rods**

Vertical ... 21/8" tubing plain steel; 3/4" rod

Horizontal ... 21/8" tubing plain steel; 3/4" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

### Well Accessories

Cathodic protection rectifier.

## **Building**

n/a



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Weyburn Well Area - Medium Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... 160 Pumping unit

• All other vertical well pumping units:

Rated Volume	Depth (ft.)			
(barrels/day)	< 3000	3000 to < 4800	4800 to < 5700	≥ <b>5700</b>
< 3	40	114	114	228
3 to < 10	57	114	114	228
10 to < 75	57	160	160	320
75 to < 120	80	160	228	320
120 to < 200	PC-120	228	320	456
≥ 200	PC-120	320	456	640
Rated volume = oil per day + (water per day $\div$ 2)				

### 2. Horizontal Wells

- New wells... 640 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 to < 200	228	
200 to < 300	456	
300 to < 450	456	
450 to < 600	640	
≥ 600	912	
Rated volume = oil per day + (water per day $\div$ 2)		

## 3. Prime Mover ... electric motor.

### Wellhead Assembly

Vertical ... threaded 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

## Tubing and Rods

Vertical ... 21/8" tubing plain steel; 3/4" rod

Horizontal ... 21/8" tubing plain steel; 3/4" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

### Well Accessories

Cathodic protection rectifier.

### **Building**

n/a



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Swift Current Well Area - Light Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications.

### Pumping Equipment

1. Vertical Wells

- New wells ... 40 pumping unit
- All other vertical well pumping units:

Rated Volume	Depth (ft.)		
(barrels/day)	< 2000	2000 to < 4500	<b>≥ 4500</b>
< 1.7	25	40	40
≥ 1.7	25	40	40
Rated volume = oil per day + (water per day $\div$ 0.67)			

#### 2. Horizontal Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 to < 200	228	
200 to < 300	456	
300 to < 450	456	
450 to < 600	640	
≥ 600	912	
Rated volume = oil per day + (water per day $\div$ 2)		

### 3. Prime Mover ... electric motor.

### Wellhead Assembly

Vertical... threaded 2000 lbs.

Horizontal... flanged 2000 lbs.

Dual wellhead for multizone completion.

### **Tubing and Rods**

Vertical ... 21/8" tubing plain steel; 5/8" rod

Horizontal ... 21/8" tubing plain steel; 3/4" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

n/a



Resource Production Equipment Subject: Well Classification

### Substitute Well Features: Swift Current Well Area - Medium Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... 114 pumping unit

• All other vertical well pumping units:

Rated Volume	Depth (ft.)		
(barrels/day)	< 2000	2000 to < 4500	≥ <b>4500</b>
< 7	40	114	114
7 to < 190	57	114	114
≥ 190	228	228	228
Rated volume = oil per day + (water per day $\div$ 1.5)			

### 2. Horizontal Wells

• New wells ... 640 pumping unit

• All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 120	160	
120 to < 200	228	
200 to < 300	456	
300 to < 450	456	
450 to < 600	640	
≥ 600	912	
Rated volume = oil per day + (water per day $\div$ 2)		

3. Prime Mover ... electric motor.

## Wellhead Assembly

Vertical ... threaded 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

## **Tubing and Rods**

Vertical ... 21/8" tubing plain steel; 5/8" rod

Horizontal ... 21/8" tubing plain steel; 3/4" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

n/a



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Swift Current Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical wells

• New wells ... 160 pumping unit

• All other vertical well pumping units ... 160 pumping unit

• Related Volume = oil per day

## 2. Horizontal Wells

• New wells ... PC-54 pumping unit

• All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)
< 180	PC-54
180 to < 500	PC-64
≥ 500	PC-80
Rated volume = oil per day + (water per day $\div$ 7)	

#### 3. Prime Mover

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

## Wellhead Assembly

Vertical ... flanged 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

### **Tubing and Rods**

Vertical ... 3½" tubing plain steel; 1" rod

Horizontal ... 31/2" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

### **Building**

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	9,160
Flow Line	n/a	



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Kindersley Well Area - Light Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... 40 pumping unit

• All other vertical pumping well units:

Rated Volume		Depth (ft.)	
(barrels/day)	< 2000	2000 to < 4500	<b>≥ 4500</b>
< 1.7	25	40	40
≥ 1.7	25	40	80
Rated volume = oil per day + (water per day $\div$ 0.67)			

### 2. Horizontal Wells

• New wells ... 456 pumping unit

• All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)
< 120	160
120 to < 200	228
200 to < 300	456
300 to < 450	456
450 to < 600	640
≥ 600	912
Rated volume = oil per day + (water per day $\div$ 2)	

### 3. Prime Mover... electric motor.

## Wellhead Assembly

Vertical ... threaded 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

#### **Tubing and Rods**

Vertical ... 23/8" tubing plain steel; 5/8" rod

Horizontal ... 21/8" tubing plain steel; 3/4" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

n/a



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Kindersley Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... 160 pumping unit

• All other vertical well pumping units ... 160 pumping unit

• Rated Volume = oil per day

### 2. Horizontal Wells

• New wells ... PC-54 pumping unit

• All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 to < 500	PC-64	
≥ 500	PC-80	
Rated volume = oil per day + (water per day $\div$ 7)		

#### 3. Prime Mover

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

## Wellhead Assembly

Vertical ... flanged 2000 lbs.
Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

### **Tubing and Rods**

Vertical ... 21/8" tubing plain steel; 1/8" rod Horizontal ... 31/2" tubing plain steel; 1" rod Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	9,160
Flow Line	n/a	



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: North Battleford (South) Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

• New wells ... PC-15 pumping unit

• All other vertical well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 30	PC-10	
30 to < 80	PC-15	
80 to < 120	PC-28	
120 to < 180	PC-54	
≥ 180	PC-64	
Rated volume = oil per day + (water per day $\div$ 3)		

### 2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 to < 500	PC-64	
≥ 500	PC-80	
Rated volume = oil per day + (water per day $\div$ 7)		

### 3. Prime Mover

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

## Wellhead Assembly

Vertical ... flanged 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

### **Tubing and Rods**

Vertical ... 31/2" tubing plain steel; 1" rod

Horizontal ... 31/2" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	9,160
Flow Line	n/a	



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: North Battleford (North) Well Area - Heavy Crude Oil Wells

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical Wells

- New wells ... PC-15 pumping unit
- All other vertical well pumping units:

Rated Volume	Depth (ft.)		
(barrels/day)	< 1000	1000 to < 2000	≥ <b>2000</b>
< 9.0	40	80	PC-15
≥ 9.0	57	PC-15	PC-15
Rated volume = oil per day + (water per day ÷ 3)			

## 2. Horizontal Wells

- New wells ... PC-54 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)
< 180	PC-54
180 to < 500	PC-64
≥ 500	PC-80
Rated volume = oil per day + (water per day $\div$ 7)	

### 3. Prime Mover

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

## Wellhead Assembly

Vertical ... flanged 2000 lbs.

Horizontal ... flanged 2000 lbs.

Dual wellhead for multizone completion.

#### **Tubing and Rods**

Vertical ... 31/2" tubing plain steel; 1" rod

Horizontal ... 31/2" tubing plain steel; 1" rod

Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

Facility Type	Building	Rate (\$/unit)
Tank	64 sq.ft. pump shack	9,160
Flow Line	n/a	



Resource Production Equipment Subject: Well Classification

# Substitute Well Features: Swift Current and Weyburn Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
Tubing	<ul> <li>1" diameter, plastic</li> <li>Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string</li> </ul>		
Wellhead assembly	<ul><li>Threaded, 1000 pound pressure</li><li>Dual wellhead for multi-zone completions</li></ul>		
Chemical equipment	60% of Type 1		
Water handling buildings	100% of Type 1		
Water handling equipment	100% of Type 1		
Metering equipment	10% of Type 1		
Rated Volume = gas per day			
Total Rate (\$)	Threaded, 1000 pound pressure	36,650	
(Excludes tubing, flow line and manifold)	Dual wellhead	38,980	

## Substitute Well Features: Kindersley Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
Tubing	<ul> <li>2¾" diameter, plain steel</li> <li>Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string</li> </ul>		
Wellhead assembly	<ul> <li>Threaded, 2000 pound pressure</li> <li>Dual wellhead for multi-zone completions</li> </ul>		
Chemical equipment	None		
Water handling buildings and equipment	65% of Type 2		
Metering equipment	80% of Type 1		
Rated volume = gas per day			
Total Rate (\$)	Threaded, 2000 pound pressure 120,700		
(Excludes tubing, flow line and manifold)	Dual wellhead 123,620		



Resource Production Equipment Subject: Well Classification

# Substitute Well Features: North Battleford (South) Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
	• 23/8" diameter, plain steel		
Tubing	• Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string		
Wellhead assembly	Threaded, 2000 pound pressure		
Weilliead assembly	Dual wellhead for multi-zone completions		
Chemical equipment	100% of Type 1		
Water handling buildings and equipment	55% of Type 2		
Metering equipment	80% of Type 1		
Rated volume = gas per day			
Total Rate (\$)	Threaded, 2000 pound pressure 110,050		
(Excludes tubing, flow line and manifold)	Dual wellhead 112,970		

## Substitute Well Features: North Battleford (North) Well Area - Gas Wells

The resource production equipment required to operate a substitute gas well that performs the same function as the gas well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
Tubing	<ul> <li>23/8" diameter, plain steel</li> <li>Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string</li> </ul>		
Wellhead assembly	<ul> <li>Flanged, 2000 pound pressure</li> <li>Dual wellhead for multi-zone completions</li> </ul>		
Chemical equipment	100% of Type 1		
Water handling buildings and equipment	48% of Type 2		
Metering equipment	80% of Type 1		
Rated volume = gas per day	Rated volume = gas per day		
Total Rate (\$)	Flanged, 2000 pound pressure 103,510		
(Excludes tubing, flow line and manifold)	Dual wellhead 112,920		



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Air, Polymer, Water and Gas Injection Wells

The resource production equipment required to operate a substitute air, water or gas injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
	• 27/8" tubing, plain steel		
Tubing	• Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string		
Wellhead assembly	Threaded, 2000 pound pressure		
Metering equipment	1 - 2" floco meter		
Control valves	1 - 3" choke		
Control valves	1 - pressure control switch		
Well accessories	Well accessories All wells east of the third meridian: cathodic protection		
Well accessories	rectifier		
Building	20 sq.ft. fibreglass wellhead shelter		
Total Rate (\$)	All wells east of the third meridian 70,710		
(Excludes tubing, flow lines and manifolds)	All wells west of the third meridian 53,440		

## **Substitute Well Features: Continuous Steam Injection Wells**

The resource production equipment required to operate a substitute continuous steam injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
Tubing	<ul> <li>3½" tubing, lined</li> <li>Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string</li> </ul>		
Wellhead assembly	Flanged, 3000 pound pressure		
Metering equipment	1 - 3" turbine meter and totalizer		
Control valves	1 - 3" choke		
Total Rate (\$) (Excludes tubing, flow lines and manifolds)		88,020	





Resource Production Equipment Subject: Well Classification

## **Substitute Well Features: Cyclic Steam Injection Wells**

The resource production equipment required to operate a substitute cyclic steam injection well that performs the same function as the injection well being valued shall be determined in accordance with the following specifications:

Description	Specifications		
	• 3½" tubing, lined; 1" rods		
Tubing and rods	• Length: depth of well for first tubing string, depth of well		
	minus 200 ft. for each additional tubing		
Pumping equipment	67% of a conventional 160 pumping unit with electric		
1 umping equipment	motor		
Wellhead assembly	Flanged, 3000 pound pressure		
Metering equipment	3 - 3" turbine meters and totalizers		
Control valves	1 - 3" choke		
Total Rate (\$)		246,170	
(Excludes tubing, rod, flow lines and manifolds)		240,170	



Resource Production Equipment Subject: Well Classification

## **Substitute Well Features: Water Source Wells**

The resource production equipment required to operate a substitute water source well that performs the same function as the water source well being valued shall be determined in accordance with the following specifications:

# Tubing and Rods

1. New Wells

- 21/8" tubing, plain steel; 1/8" rod
- Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string
- 2. Rated volume < 150,000 imp. gal./day
  - 21/8" tubing, plain steel; 1/8" rod
  - Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string
- 3. Rated volume  $\geq 150,000$  imp. gal./day
  - 21/8" tubing plain steel
  - Length: depth of well for first tubing string, depth of well minus 200 ft. for each additional tubing string for depth of well

		Specifications		
	Description	New Wells and Wells Rated Volume < 150,000 imp. gal./day	Rated Volume ≥ 150,000 imp. gal./day	
	Pumping equipment	<ul> <li>PC-15 pumping unit</li> <li>50% of 1 - variable frequency drive</li> </ul>	<ul> <li>Submersible pumping unit 400 series 100 stage</li> <li>Submersible pump motor 456 series 80 hp</li> <li>Switchboard 100 hp</li> <li>Transformer 75 kva</li> <li>Size 4 submersible pump cable x well depth x 1.05</li> <li>50% of 1 - variable frequency drive</li> </ul>	
	Wellhead assembly	Threaded, 2000 pound pressure	Threaded, 2000 pound pressure	
	Metering equipment	None	None	
	Control valves	<ul><li>1 - 3" choke</li><li>1 - pressure control switch</li></ul>	<ul><li>1 - 3" choke</li><li>1 - pressure control switch</li></ul>	
	Well accessories: cathodic protection	All wells east of the third meridian	All wells east of the third meridian	
	Building	None	20 sq.ft. fibreglass wellhead shelter with heat	
Total Rate (\$)	All wells east of the third meridian	179,750	282,230	
(Excludes tubing, rod, cable, flow lines and manifolds)	All wells west of the third meridian	162,480	264,960	



Resource Production Equipment Subject: Well Classification

## Substitute Well Features: Heavy Crude Steam Assisted Gravity Drainage (SAGD) Oil Wells (entire Province)

The resource production equipment required to operate a substitute oil well that performs the same function as the oil well being valued shall be determined in accordance with the following specifications:

### Pumping Equipment

1. Vertical SAGD Wells

• New wells ... PC-15 pumping unit

• All other vertical well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 30	PC-10	
30 to < 80	PC-15	
80 to < 120	PC-28	
120 to < 180	PC-54	
≥ 180	PC-64	
Rated volume = oil per day + (water per day $\div$ 3)		

### 2. Horizontal SAGD Wells

- New wells ... 456 pumping unit
- All other horizontal well pumping units:

Rated Volume (barrels/day)	All Depths (ft.)	
< 180	PC-54	
180 to < 500	PC-64	
500 to < 600	320	
600 to < 800	456	
≥ 800	640	
Rated volume = oil per day + (water per day $\div$ 7)		

### 3. Prime Mover

Facility Type	Prime Mover
Tank	Gas Motor
Flow Line	Electric Motor

### Wellhead Assembly

Vertical ... flanged 3000 lbs. Horizontal ... flanged 3000 lbs.

Dual wellhead for multizone completion.

### **Tubing and Rods**

Vertical ... 3½" tubing plain steel; 1" rod Horizontal ... 4½" tubing plain steel; 1" rod Length ... depth of well for first tubing string

... depth of well minus 200 ft. for each additional tubing string

## **Building**

Facility Type	Building	Rate (\$)
Tank	64 sq.ft. pump shack	9,160
Flow Line	n/a	



uipment Subject: Wellhead Assembly

# Description

A typical wellhead assembly is made up of a casing head, tubing head and Christmas tree. The wellhead may be screwed onto the casing or it may be an assembly that is bolted together. These are called the threaded or flanged wellheads respectively.

## Rates

The rates for well head assembly are dollars per unit.

	Size						
Туре	Series 400 W.P. ≤ 1000 psi	Series 600 W.P. 2000 psi	Series 900 W.P. 3000 psi	Series 1500 W.P. 5000 psi			
Pumping Oil or Wate	Pumping Oil or Water						
Single Flanged	19,230	22,100	22,900	37,370			
Single Threaded	16,930	19,190	19,840	31,860			
Dual Flanged	33,870	38,970	41,100	41,570			
Dual Threaded	19,160	30,000	35,620	35,440			
Flowing Oil & Gas							
Single Flanged	22,190	27,630	35,850	35,900			
Single Threaded	17,750	25,300	32,440	32,730			
Dual Flanged	30,790	37,040	43,470	43,500			
Dual Threaded	20,080	28,220	31,560	31,640			
Injection - Air, Polyn	ner, Water and Gas						
Flanged	22,280	27,630	36,500	36,500			
Threaded	17,600	25,300	32,940	32,730			
Dual Threaded	20,080	28,220	31,560	31,640			
Injection - Steam							
Flanged	48,620	48,230	48,030	48,030			
Steam Injection & Pumping							
Flanged	69,460	69,000	68,650	68,510			
Tubingless (Casing Head)							
Flanged	17,160	18,860	18,640	18,960			
Threaded	11,440	12,110	12,570	12,840			



Subject: Wellhead Assembly



Resource Production Equipment Subject: Pumping Units

## Conventional and Hydrabeam

This is the typical horsehead or grasshopper counterbalance unit. The rods are raised by carrier bar at the horsehead end of the waling beam. On the downstroke, the weight of the rod assembly is counterbalanced by large weights. The pivot point of the assembly is in the middle of the walking beam.

## Rates

The rates for conventional and hydrabeam pumping units are in dollars per unit.

Gear Box Torque	Without Prime		ectric	_	as (1)
Rating (x 1000) (lb.)	Mover (2)	Prime I	Mover (1)	Prime Mover (1)	
		Rate	Range (hp)	Rate	Range (hp)
25	47,190	59,600	5	101,720	9 - 12
40	52,430	63,950	6	104,900	9 - 12
57	62,430	75,400	5 - 10	120,750	9 - 12
80	67,410	81,100	5 - 10	131,160	9 - 19
114	111,970	123,540	7.5 - 15	181,820	13 - 19
160	122,200	133,770	15 - 25	202,200	20 - 29
228	144,310	161,960	20 - 40	242,320	20 - 39
320	172,990	188,750	30 - 60	296,940	30 - 59
456	215,210	234,040	40 - 75	357,540	40 - 99
640	249,170	270,160	50 - 75	433,190	60 - 99
912	293,940	322,560	60 - 100	516,780	60 - 149
1280	475,950	508,730	70 - 125	720,200	100 - 199

### Rates include:

- prime mover where noted

- belt

- rod rotator

concrete base

- bottom hole pump

- frame extension and side rails

- polish rod

- beam chemical injector at 50%

- counter weights

- pressure switch

stuffing box

- installation

### NOTE: 1) Costs include:

- per electrified site \$12,540
- per gas operated site propane vessel and/or scrubber with self-feed gas at \$14,920
- 2) Cost without Prime Mover:
  - electrical and propane vessel costs are not included and must be added if these rates are used.
  - apply these rates to non-typical installations
- 3) Strap jacks and slant jacks:
  - increase conventional pumping unit cost by 20%



Resource Production Equipment Subject: Pumping Units

### Unitorque and Air-Balanced Beam

The entire walking beam for unitorque and air-balanced beam pumping units moves up and down with the pivot point at the end of the beam. Unitorque pumping units have a counterweight system similar to conventional pumping units. The air-balanced beam pumping units have no counterweights. The downstroke is cushioned by a very large air-supplied "shock absorber". There will be a small compressor mounted on the pumping unit to feed the unit.

#### Rates

The rates for unitorque and air-balanced beam pumping units are dollars per unit.

Gear Box	Without	Electric Prime Mover (1)		Gas Prime Mover (1)	
Torque Rating (x 1000) (lb.)	Prime Mover (2)	Rate	Range (hp)	Rate	Range (hp)
114	122,720	134,290	7.5 - 15	180,680	13 - 19
160	148,650	160,220	15 - 25	226,650	20 - 29
228	172,040	189,690	20 - 40	269,730	20 - 39
320	203,410	222,350	30 - 60	332,470	30 - 59
456	238,800	262,230	40 - 75	392,820	40 - 99
640	265,590	291,430	50 - 75	507,540	60 - 99
912	324,510	362,430	60 - 100	592,130	60 - 149

#### Rates include:

- prime mover where noted
- belt
- rod rotator
- concrete base
- bottom hole pump
- frame extension and side rails
- polish rod
- beam chemical injector at 50%
- counter weights
- pressure switch
- stuffing box
- installation

## NOTE: 1) Costs include:

- per electrified site \$12,500
- per gas operated site propane vessel and/or scrubber with self-feed gas at \$14,870
- 2) Cost without Prime Mover:
  - electrical and propane vessel costs are not included and must be added if these rates are used
  - apply these rates to non-typical installations



Resource Production Equipment Subject: Pumping Units

## **Submersible Pumping Equipment**

Submersible pumps have the major working system suspended at the bottom of the well bore inside the tubing. This system is identified on the surface by heavy electric cable emerging from the top of the wellhead.

### Motor Rates

The motor rates for submersible pumping equipment are in dollars per unit.

Rating (hp)		Rate	
Series	375	456	540
Minimum Casing	4½"	5½"	65/8"
7.5	50,760	47,750	
10.0	59,760	51,080	
15.0	66,900	56,420	
19.5	71,710	62,510	
22.5	75,610	66,790	
25.0	84,620	68,980	
30.0		74,670	59,030
40.0		86,100	63,770
50.0		98,030	72,180
60.0		102,750	82,010
70.0		113,410	88,570
80.0		124,420	96,180
90.0		135,250	102,880
100.0		145,020	107,810
110.0		155,070	114,260
120.0		164,430	120,330
130.0			128,650
150.0			142,930
160.0			151,540
180.0			166,830
200.0			183,160
225.0			200,690

NOTE: 1) Series number refers to outside diameter size of motor or pump, eg. series 456 is 4.56 inches O.D.

- 2) Motors and pumps can be stacked, eg. in 4½" casing, to achieve 100 hp, 4 25 hp motors are stacked.
- 3) Generally, the pump is the value of the motor. This can be used as a guide if proper size information is not available.



Resource Production Equipment Subject: Pumping Units

# Pump Rates

The pump rates for submersible pumping equipment are in dollars per unit.

Stages	Length (ft.)	Rate			
Series		338	400	540	540
Barrels/Day		400-1500	280-4000	2000-7000	10000
Minimum Casing		41/2"	5½"	65/8"	65/8"
<u>≤</u> 20	2.1	17,170	17,000	16,890	16,560
21 - 40	3.5	21,250	17,170	21,850	29,880
41 - 60	4.9	25,450	20,030	25,250	34,750
61 - 80	6.3	29,460	23,240	28,390	39,490
81 - 100	7.8	33,370	26,150	31,600	43,950
101 - 120	9.1	37,150	29,060	34,720	50,460
121 - 140	10.5	40,970	31,970	37,810	53,080
141 - 160	11.9	44,370	34,370	40,420	56,860
161 - 180	13.3	47,590	36,780	43,030	60,490
181 - 200	14.7	50,620	39,110	45,330	63,960
201 - 220	16.1		42,010	48,550	68,690
221 - 240	17.5		44,990	51,780	73,290
241 - 260	18.9			58,020	77,910
261 - 280	20.4			61,390	82,610
> 280	21.8			64,900	87,270

# Switchboards

The switchboard rates for submersible pumping equipment are in dollars per unit.

Rating (hp)	Rate
25	18,600
50	21,060
100	24,530
200	37,340
1000	62,250
1500	63,960
2000	65,790



Resource Production Equipment Subject: Pumping Units

# **Transformers**

The transformer rates for submersible pumping equipment are in dollars per unit.

Size (kVA)	Rate
50	15,160
75	15,990
100	21,070
125	22,740
150	27,750
200	39,580
250	42,940

## Cable

The cable rates for submersible pumping equipment are in dollars per linear foot.

Size	Power (hp)	Rate
1	> 200	42.69
2	150 - 200	37.03
4	< 150	27.70

## **Progressive Cavity (PC)**

## Pump Rates

The pump rates for progressive cavity pumping units are in dollars per unit.

Size (m <sup>3</sup> /100 rpm)	Rate
10	87,070
12	89,330
15	92,220
28	96,840
54	104,840
64	114,190
80	118,480
95	121,410
120	142,830
	· · · · · · · · · · · · · · · · · · ·

## Rates Include:

- drive system (gas or electric prime mover, hydraulic or electric skid)
- bottom hole pump (rotor, stator)
- installation

## Variable Frequency Drive

The rate for a variable frequency drive shall be \$66,520 per unit.





Resource Production Equipment Subject: Pumping Units



Resource Production Equipment Subject: Prime Movers

# Description

Prime movers include electric and gas motors used to provide power to pumping units.

## **Triple-Rated Motors**

The triple-rated motor prime mover rates are in dollars per unit.

Size		Controller	Data
(hp)	(kW)	Size	Rate
10.0 / 7.5 / 5.0	7.5 / 5.6 / 3.7	1	9,280
15.0 / 10.0 / 7.5	11.2 / 7.5 / 5.6	2	12,820
20.0 / 15.0 / 10.0	14.9 / 11.2 / 7.5	2	14,080
25.0 / 20.0 / 15.0	18.6 / 14.9 / 11.2	2	17,090
30.0 / 25.0 / 15.0	22.4 / 18.6 / 11.2	3	18,730
40.0 / 30.0 / 20.0	29.8 / 22.4 / 14.9	3	23,420
50.0 / 40.0 / 30.0	37.3 / 29.8 / 22.4	3	27,150
60.0 / 50.0 / 40.0	44.8 / 37.3 / 29.8	4	31,460
75.0 / 60.0 / 50.0	56.0 / 44.8 / 37.3	4	38,340
100.0 / 75.0 / 60.0	74.6 / 56.0 / 44.8	4	43,790
125.0 / 100.0 / 75.0	93.3 / 74.6 / 56.0	4	46,010

## Rates include:

- 3 phase

- 1200 RPM

- fan-cooled motor

- 60 Hz

- class F insulation

- controller

- 460 volt

- totally enclosed

installation



Resource Production Equipment Subject: Prime Movers

# **Single-Rated Motors**

The single-rated motor prime mover rates are in dollars per unit.

Size (hp)	Rate
1.0 - 2.0	6,700
3.0 - 5.0	7,000
7.5 - 10.0	8,110
15.0 - 20.0	11,570
25.0 - 30.0	14,850
40.0	17,650
50.0	18,940
60.0	23,420
75.0	25,850
100.0	37,920
125.0	43,100
150.0	48,660
200.0	64,320
250.0	77,170
Rates include:	
- 3 phase	- controller
- 1200 RPM	- 460 volt
<ul> <li>fan-cooled motor</li> </ul>	<ul> <li>totally enclosed</li> </ul>
- 60 Hz	<ul> <li>installation</li> </ul>
<ul> <li>class F insulation</li> </ul>	

# **Gas Engines**

The gas engine prime mover rates are in dollars per unit.

Group #	Size (hp)	Rate	
1	9 - 12	44,130	
2	13 - 19	57,960	
3	20 - 29	78,000	
4	30 - 39	97,690	
5	40 - 59	129,060	
6	60 - 99	154,010	
7	100 - 149	241,960	
8	150 - 199	267,630	
NOTE: Deduct \$4,530 if no electric starter in groups #1 to #4.			
Rates include:			
- twin-disk cl	utch	<ul> <li>power take off</li> </ul>	
<ul> <li>condensing radiator with fan</li> </ul>		<ul> <li>heavy flywheel</li> </ul>	
- pressure lubrication		<ul> <li>regulator</li> </ul>	
<ul> <li>combination gas-gasoline carburetor</li> </ul>		<ul> <li>air cleaner</li> </ul>	
- adjustable sub-base		<ul> <li>engine starter</li> </ul>	
- miscellaneo	us pipe fittings	<ul> <li>installation</li> </ul>	



Resource Production Equipment Subject: Tubing and Rods

# Description

The bottom hole pump is suspended from the surface by a series of 20 foot steel or fibreglass rods that are threaded together. The most common size for the tubing is 2% inches (plain) in diameter and for the rod it is % inches in diameter.

#### Rates


The rates for tubing and rods are dollars per lineal foot.

## **Tubing**

Sizo (in )	Steel		Plastic
Size (in.)	Plain	Lined	Flastic
<u>≤</u> 1½	7.10		2.52
2	7.89		
23/8	8.55	9.54	
27/8	9.76	17.28	
31/2	13.62	18.76	
4	18.25	23.47	
41/2	24.58	30.14	

## Rods

Size (in.)	Rate
5/8	3.47
3/4	4.30
7/8	5.41
1	6.47





Resource Production Equipment Subject: Tubing and Rods



Resource Production Equipment Subject: Separators

## Description

A separator is a vertical or horizontal vessel through which the emulsion is passed to split liquids and gases. Centrifugal action created by baffles inside the unit causes the split to occur.

## **Vertical Two-Phase Separators**

The rates for vertical two-phase separators are in dollars per unit.

Diameter (in )	Height (ft.)	
Diameter (in.)	6	
125-260 psi Working Pressure		
≤ 16	24,740	
$> 16 \text{ to} \le 24$	46,610	
$> 24 \text{ to} \le 36$	75,610	
$> 36 \text{ to} \le 48$	110,570	
$> 48 \text{ to} \le 60$	139,390	
Rates include:		
<ul> <li>1 oil dump valve</li> </ul>	<ul> <li>1 gauge glass assembly</li> </ul>	
<ul> <li>1 liquid level controller</li> </ul>	- 1 safety relief valve	
<ul> <li>1 pilot gas supply regulator</li> </ul>	- 1 pressure gauge	

## **Vertical Three-Phase Separators**

The rates for vertical three-phase separators are in dollars per unit.

Diameter (in )	Height (ft.)	
Diameter (in.)	8	
500-1000 psi Working Pressure		
≤ 16	54,680	
$> 16 \text{ to} \le 24$	68,070	
$> 24 \text{ to} \le 36$	98,790	
$> 36 \text{ to} \le 42$	142,270	
Rates include:		
- 2 oil and water dump valves	- 1 safety relief valve	
<ul> <li>1 oil level controller</li> </ul>	- 1 pressure gauge	
<ul> <li>1 pilot gas supply regulator</li> </ul>	- 1 water level controller	
- 1 gauge glass assembly		



Resource Production Equipment Subject: Separators

# **Horizontal Two-Phase Separators**

The rates for horizontal two-phase separators are in dollars per unit.

Diameter (in )	Length (ft.)
Diameter (in.)	10
125-260 psi Working Pressure	
≤ 16	39,230
> 16 to ≤ 24	54,340
> 24 to ≤ 36	69,920
> 36 to ≤ 48	80,750
$> 48 \text{ to} \le 60$	87,240
Rates include:	
- 1 oil dump valve	- 1 gauge glass assembly
- 1 liquid level controller	- 1 safety relief valve
<ul> <li>1 pilot gas supply regulator</li> </ul>	- 1 pressure gauge

# **Horizontal Three-Phase Separators**

The rates for horizontal three-phase separators are in dollars per unit.

Diameter (in )	Length (ft.)	
Diameter (in.)	15	
500-1000 psi Working Pressure		
≤ 16	64,620	
> 16 to ≤ 24	86,960	
> 24 to ≤ 36	115,330	
> 36 to ≤ 48	154,850	
> 48 to ≤ 60	198,990	
Rates include:		
- 2 oil and water dump valves	- 1 gauge glass assembly	
- 1 oil level controller	<ul> <li>1 safety relief valve</li> </ul>	
<ul> <li>1 pilot gas supply regulator</li> </ul>	- 1 pressure gauge	
- 1 water level controller		



Resource Production Equipment Subject: Heater and Heat Exchanger

## Description

Heaters and heat exchangers are used to prevent line and equipment from freezing.

### Heaters

The rates for direct and indirect heaters are in dollars per unit.

Output Range (BTU)	Rate	
	Indirect	Direct
50,000 - 170,000	57,460	50,160
171,000 - 375,000	58,760	51,920
376,000 - 625,000	64,020	55,340
626,000 - 875,000	71,620	58,830
876,000 - 1,250,000	82,610	70,120
1,251,000 - 1,750,000	98,060	85,530
1,751,000 - 2,500,000	108,060	91,500
2,501,000 - 3,500,000	138,950	130,670
3,501,000 - 4,500,000	168,200	132,220

### Rates include:

- fire tube
- thief hatch
- skid
- temperature control and high temperature shut down
- flame arrestor and stack
- expansion pot c/w instruments
- soil (not included with direct)
- fuel gas manifold c/w burning
- installation



Resource Production Equipment Subject: Heater and Heat Exchanger

# **Tubular and Rectangular Plate Heat Exchangers**

The rates for tubular and rectangular plate heat exchangers are in dollars per cubic foot.

Face Area (sq.ft.)	Rate (\$/cu.ft.)		
<u>≤</u> 2	2,837		
3	2,725		
4	2,647		
6	2,450		
8	2,253		
10	2,070		
12	1,936		
14	1,683		
Rates include:	Rates include:		
<ul> <li>standard unit sta</li> </ul>	inless steel plates		
<ul> <li>installation</li> </ul>			
Sample Calculation:	ample Calculation:		
Face Area $= 3$	Area = 3  ft.  x  4 ft.		
Length $= 8$	= 8 ft.		
Volume = 3			
= 9	= 96 cu.ft.		
Rate $=$ \$	= \$1,936 /cu.ft.		
Value = V	= Volume x Rate		
= 9	$= 96 \text{ cu.ft. } \times 1.936/\text{cu.ft.}$		
= \$	= \$185,860		



Resource Production Equipment Subject: Meters

## Description

Meters are used to calibrate the pressure and volume of a liquid or gas flowing through a flow line or at a gas well.

## **Dry Flow Meters**

The rates for dry flow meters are in dollars per unit.

Туре	Rate
Gas, Dry Flow Recorder Chart 100" (≤ 1000 psi)	
1 or 2 pen	7,870
3 pen	10,200

## **Orifice Fittings and Meter Runs**

The rates for orifice fittings and meter runs are in dollars per unit.

Size (in.)	Rate
Senior Quick Change (100 - 600 psi)	
2	11,340
3	13,020
4	15,380
6	19,850
8	23,680
10	28,030
Simplex (150 - 600 psi)	
2	3,040
3	3,780
4	4,620
6	6,840
8	8,830
10	10,720

#### Rates include:

- orifice fittings
- regulator
- pipes
- valves and fitting for meter run
- installation

## **Net Oil Computer and Micro Motion Meter**

The rates for net oil computer and micro motion meters are in dollars per unit.

Inlet Size (in.)	Rate
2	52,650
3	55,400
4	66,700

### Rates include:

- capacitance probe
- indicator
- installation



Resource Production Equipment Subject: Meters

## **Positive Displacement Meter**

The rates for positive displacement meters are in dollars per unit.

Line Size (in.)	Rate
Floco Meter	
≤ 2	6,990
3 to 4	10,100
Sampler	4,880
Digital Meter	
1	9,090
2 w/cubic meter readout	12,200

### **Turbine Meters and Totalizer**

The rates for turbine meters and totalizers are in dollars per unit.

Size (in.)	Rate
<u>≤</u> 2	21,770
3	23,950
Rates include:	
- meter	- fittings
- pipes	<ul> <li>miscellaneous valves</li> </ul>
<ul> <li>totalizer</li> </ul>	<ul> <li>installation</li> </ul>

# **Cabinet Type Meter Housing (Meter Cabinet)**

The rate for a meter cabinet is in dollars per unit.

Туре	Rate	
Meter Cabinet	24,700	
Includes:		
<ul> <li>1-2 pen dry flow recorder</li> </ul>		
<ul> <li>2 door shed</li> </ul>	2 door shed	
<ul> <li>small separa</li> </ul>	small separator and associated	
equipment		
<ul> <li>lines, valves</li> </ul>	- lines, valves, meters, gauges, etc.	
<ul> <li>installation</li> </ul>	- installation	
- freight	freight	



Resource Production Equipment Subject: Valves and Controls

## Description

A valve is a device used to control the rate of flow in a line, to open or shut off a line completely, or to serve as an automatic or semi-automatic safety device.

#### Valves

The rates for valves are in dollars per unit.

### Desurgers

Size (in.)	Rate
<u>≤</u> 2	10,810
3	14,670
4	18,060

## High-low Pressure Shutdown

High-low pressure shutdowns are valued at \$2,450 per unit.

# Surface Safety Valves

Туре	Typical Model	Rate
	Willis HYG 20 3000#	18,250
Hydr/Elect. actuating	Willis HYG 30 3000#	18,250
	Willis HYG 40 3000#	18,250
D . 1 1		

### Rates include:

- valve
- actuator and fittings
- installation

## Pressure Control Switch

Type	Rate
Presco, Murphy	1,770

### Choke

The rates for chokes are in dollars per unit.

Type	Size (in.)	Rate
Low pressure and low volume	<u>≤</u> 2	1,880
High pressure and high volume	3 - 6	16,040





Resource Production Equipment Subject: Valves and Controls



Resource Production Equipment Subject: Pumps

# Description

A pump is used to increase the pressure on a fluid in order to move the fluid through a pipe.

### Rates

The rates for pumps are in dollars per unit.

### Centrifugal Pump

Inlet Size (in.)	Rate
1	5,500
2	6,450
3	7,270
4	7,760
5	9,070
6	10,770

## **Progressive Cavity**

Inlet Size (in.)	Rate
1	5,560
2	7,990
3	10,280
4	15,610
6	18,240
8	24,120

# NOTE:

- 1) Add for prime movers
- 2) The rates above are for 1 stage pumps.

  To determine the 2 and 3 stage pump rates, 12% of the 1 stage pump rate is added to each subsequent stage.

## Rate include:

- pump
- base
- valves and fittings
- installation



Resource Production Equipment Subject: Pumps

# Reciprocating (Plunger) Pumps

	Rate		
Input (hp)	Simplex/ Duplex	Triplex	Quintuplex
3	48,950		
5	49,690		
10	54,480		
< 21		59,340	70,770
21 - 40		74,680	89,120
41 - 70		107,330	173,610
71 - 100		156,110	187,900
101 - 150		191,520	283,210
151 - 250		264,820	291,730
> 250		473,090	476,120

## Rates include:

- pump
- base
- prime mover
- installation

# Transformer and Injection Pumps

Size (hp)	Rate
10	119,000
20	125,150
30	131,290
50	143,620
100	176,330
250	275,240
500	439,260
750	602,690
1000	765,660

## Rates include:

- motor
- thrust chamber
- intake section
- pump
- shutdown switches
- skid
- installation





Resource Production Equipment Subject: Chemical Injectors

# Description

Chemical injectors are used to add chemicals to prevent freezing, plugging or corrosion or to assist in whatever process is being carried out in the treatment or other cycle.

### Rates

The rates for chemical injectors are in dollars per unit.

Description	Size (hp)	Rate
Electric motor driven	<u>≤</u> 2	9,970
(add for tanks > 60 imp. gal.)	3 and 5	25,200
Multiple head proportioning pump		10,260
Air/gas driven		5,740
Alcohol drip (9 imp. gal. tank)		2,020





Resource Production Equipment Subject: Chemical Injectors



Resource Production Equipment Subject: Compressors

# Description

Compressors are used to supply air pressure to operate valves, fire flood wells and to transport gas in a flow line.

## **Instrument Air Compressors**

The rates for instrument air compressors are in dollars per unit.

Si	Size		
(hp)	(kW)	Rate	
≤ 10	≤ 7.46	45,370	
11 - 15	8.20 - 11.19	62,840	
16 - 20	11.93 – 14-91	85,810	
> 20	> 14.91	93,670	

### Rates include:

- air receiver
- explosion-proof motor
- dryer and after cooler
- installation

### **Injection Air Compressors**

The rates for injection air compressors are in dollars per unit.

Size (hp)	Rate
400	1,417,970
550	1,812,570
1000	2,881,160
2000	3,258,380
3000	3,863,410
4000	4,546,950
Rates include:	
- air intake, coolers	- valves
<ul> <li>fittings and equipment</li> </ul>	<ul> <li>concrete base</li> </ul>
<ul> <li>engine or electric motor</li> </ul>	or - installation
<ul> <li>miscellaneous pipes</li> </ul>	

- metering and controls



Resource Production Equipment Subject: Compressors

### **Natural Gas Compressors**

The rates for natural gas compressors are in dollars per horsepower unit.

Description	Rate
Turbine engine/centrifugal (gas plant)	10,530
Reciprocating engine (gas plant)	7,490
Reciprocating or electric (field gathering)	4,990

### Rates include:

- building
- gauge board
- filters
- electrical equipment
- atmospheric-type jacket water cooler
- free air and exhaust duct
- scrubber
- supports
- electrical substation
- skid or concrete base
- suction or discharge bottles
- compressor
- conductors and conduit
- central panel
- pumps
- intake or exhaust silencer
- main switchboard
- installation





Resource Production Equipment Subject: Cathodic Protection Rectifiers

# Description

Cathodic protection uses a rectifier with a network of wires and anodes installed to create an electric field around flow lines and casing in corrosion prevention.

#### Rates

The rates for cathodic protection rectifiers are in dollars per unit.

Size (amperage)	Rate
Single well (12 - 16)	17,270
Field system (17 - 25)	25,680
Th. 1 1 1	

#### Rates include:

- rectifier
- conduit and fittings
- 2" x 60" steel anodes
- cadwelds and handicap
- cables
- splice kits and connectors
- installation





Resource Production Equipment Subject: Cathodic Protection Rectifiers





Resource Production Equipment Subject: Control Panels

# Description

Control panels are switches and other devices used to start, stop, measure, monitor or signal the operation of equipment.

## Rates

The rates for control panels are in dollars per unit.

Power Rating		Rate	
(hp)	(kW)	Kate	
<u>≤</u> 50	< 38	43,470	
51 - 450	38 - 336	96,270	
451 - 850	337 - 634	166,670	
851 - 1500	635 - 1119	289,320	
1501 - 2500	1120 - 1865	380,130	
2501 - 4000	1866 - 2984	463,170	

## Rates include:

- relays
- control circuit gauges
- installation





Resource Production Equipment Subject: Control Panels



Resource Production Equipment Subject: Steam Generators

# Description

Steam generators are used to inject steam to the producing formation for enhanced oil recovery systems.

## Rates

The rates for steam generators are in dollars per unit.

Description	Rate
10,000,000 BTU/hr. unit	
Generator	1,412,390
Water softener and filter	110,560
Trailer	183,360
Building (on trailer)	117,820
Total for Unit	1,824,130
18,500,000 BTU/hr. unit	
Generator	1,411,450
Water softener and filter	110,260
2 Trailers (soft and gen)	286,700
2 Buildings (on trailer)	202,440
Total for Unit	2,010,850
22,000,000 BTU/hr. unit	
Generator	1,451,950
Water softener and filter	123,350
2 Trailers (soft and gen)	268,050
2 Buildings (on trailer)	177,410
Total for Unit	2,020,760
25,000,000 BTU/hr. unit	
Generator	1,605,720
Water softener and filter	132,130
1 Trailers	226,650
1 Buildings	103,370
Total for Unit	2,067,870
50,000,000 BTU/hr. unit schedule 80 to 160	
1,750 to 2,400 psi	
Base, installation, tie-in	2,680,640
Generator	2,947,520
Water softeners and filters	248,810
Materials and accessories	444,170
Total for Unit	6,321,140





Resource Production Equipment Subject: Steam Generators

Description	Rate
$\geq 100,000,000$ BTU/hr. unit schedule 80 to 160	
1,750 to 2,400 psi	
Base, installation, tie-in	2,935,560
Generator	4,109,130
Water softeners and filters	341,520
Materials and accessories	443,310
Total for Unit	7,829,520
Rates include:	
- softeners	

- filters
- accessories
- installation



Resource Production Equipment Subject: Filters

# Description

Filters are used for cleaning water.

## **Sand Filter**

The rates for sand filters are in dollars per tank unit.

Tank Size (in.)	Imp. Gal. per Minute	Pipe Size (in.)	Rate
20 x 54	30	1½	24,810
24 x 54	40	1½	28,360
30 x 60	60	2	38,090
36 x 60	90	2½	49,270
42 x 60	120	3	76,790
48 x 60	150	3	91,730
60 x 60	250	4	132,410
72 x 60	420	6	198,580
84 x 60	580	6	259,850

### **Carbon Filter**

The rates for carbon filters are in dollars per tank unit.

Tank Size (in.)	Imp. Gal. per Minute	Pipe Size (in.)	Rate
20 x 54	10	1½	22,740
24 x 54	15	1½	26,470
30 x 60	25	2	32,000
36 x 60	35	2	42,180
42 x 60	50	2½	60,450
48 x 60	65	2½	70,610
60 x 60	100	3	94,940

Rates include:

- concrete base

- miscellaneous pipes

- values and fittings

- installation





Resource Production Equipment Subject: Filters



Resource Production Equipment Subject: Industrial Water Softeners

# Description

Water softeners are used to soften the water for steam generators.

### Rates

The rates for industrial water softeners are in dollars per tank unit.

### Single Unit

Softener Tank Brine Tan	Brine Tank	Imp Cal	Pipe Size (in.)	Rate	
Width (in.) x Height (in.)	Width (in.) x Height (in.)	Imp. Gal. per Minute		Single Units	Duplex Units
20 x 54	24 x 80	55	2	31,880	64,060
24 x 54	30 x 48	75	21/2	38,340	77,040
30 x 60	38 x 48	125	3	50,900	102,210
36 x 60	42 x 48	175	4	69,940	140,530
48 x 60	48 x 60	150	3	78,330	157,190
54 x 60	54 x 60	275	4	92,120	184,940
60 x 60	60 x 60	400	4	106,800	214,530
72 x 60	72 x 60	560	6	159,530	320,340
84 x 60	84 x 60	760	6	212,330	426,550

#### Rates include:

- time clock control

- specific gravity meter

- injectors

- valves and fittings

- liquid level control

- hardness monitor

- concrete base

- water meters

- chemical

- miscellaneous pipes

- installation

Rates do not include pumps and motors.





Resource Production Equipment Subject: Industrial Water Softeners



Resource Production Equipment Subject: Flow Lines and Service Lines

### **Description**

A flow line is a line of pipe used to transport or conduct oil or gas within a well site to a battery or gas handling site, satellite, gas plant, compressor station, or other facility at which the oil or gas is prepared for pipeline transport.

A service line is a line of pipe used to transport water from a water source well or to transport fuel gas to an oil well site prime mover or to transport water, steam, air, oxygen, acid or carbon dioxide to enhance the recovery of oil from an oil well.

### Oil, Gas, Water and Air Lines

The rates for oil, gas, water and air lines are in dollars per lineal foot.

Line Sine (in )	Rate				
Line Size (in.)	Plastic	Plastic Steel			
1	10.27	25.00			
2	12.06	27.51	25.57		
3	16.55	33.11	33.25		
4	21.76	38.05	44.60		
6	36.95	51.91	78.83		
8	52.47	70.28	123.35		
10	70.84	94.68	150.28		
12	90.68	114.82	183.90		
14	107.90	124.55	217.52		

## Rates include:

- construction contract
- land right-of-way
- pipe
- exterior coating
- damages and pre-staking
- engineering
- radiographic inspection
- legal survey

### **Internal Coated Pipes**

The rates for internal coated pipes are in dollars per lineal foot.

Pipe Size (in.)	Rate
2	69.55
3	86.11
4	104.87
6	155.03
8	205.11



Resource Production Equipment Subject: Flow Lines and Service Lines

# **Steel Pipe with Polyethylene Liner**


The rates for steel pipe with polyethylene liner are in dollars per lineal foot.

Pipe Size (in.)	Rate
2	58.93
3	66.26
4	75.15
6	102.91
8	128.08
10	159.92
12	202.34
14	240.47

## **Steam Service Lines**

The rates for steam service lines are in dollars per lineal foot.

Pipe Size (in.)	Rate
1	81.72
2	92.87
3	95.50
4	99.84
6	129.47
8	156.11





Resource Production Equipment Subject: Manifolds

# Description

Manifolds are systems of headers and branch piping that can be used to gather or distribute fluids. Typically manifolds include valves for controlling the on/off flow of fluids.

### Rates

The rates for manifolds are in dollars per manifold.

Rate
3,910
9,690
13,980
19,140
27,650
39,530
57,260
82,720
119,420





Resource Production Equipment Subject: Manifolds



Resource Production Equipment Subject: Scraper Traps

# Description

Scraper traps are used to insert scrapers to clean out the flow lines and service lines.

### Rates

The rates for scraper traps are in dollars per trap or injection unit.

## Receiving and Launching Traps

Line Sine (in )	Rate	
Line Size (in.)	With Bypass	Without Bypass
2	13,720	6,480
3	16,520	7,960
4	19,220	9,230
6	28,810	
8	37,160	
10	53,330	
12	67,560	

# **Automatic Pig Injection**

Line Size (in.)	Rate
2	20,390
3	32,720
4	53,130

## Rates include:

- valves
- miscellaneous pipe and fittings
- installation





Resource Production Equipment Subject: Scraper Traps



Resource Production Equipment Subject: General Rules

#### **Summary**

This section describes the formulas, rules and principles for determining the assessed value of mine resource production equipment.

#### **Definitions**

Mine resource production equipment includes the fixtures, machinery, tools, railroad spur tracks, and other appliances used to extract and produce the ore but does not include equipment used to process or refine the ore.

Shaft linings, safety equipment, shop tools for maintenance service, spare parts, and surplus equipment are not resource production equipment by which a mine is operated.

#### Formulas, Rules and Principles

The assessed value of mine resource production equipment shall be determined by the replacement cost method established in this section. The replacement cost new shall be determined using the unit-in-place method or the trended original cost method.

The replacement cost of continuous belt conveyors over 1,000 feet in length, and solution mining resource production equipment shall be determined by the unit-in-place method. The unit-in-place base rates account for all direct and indirect costs. No additional adjustments shall be made to the base rates.

The unit-in-place base rates for solution mining resource production equipment shall be determined in accordance with the rates schedules in Chapter 4 – Resource Production Equipment, Section 4.1 – Oil and Gas Well Resource Production Equipment.

The trended original cost shall include all direct and indirect costs. Direct costs include materials, labour, supervision, equipment rentals, and utilities. Indirect costs include architectural and engineering fees, building permits, title and legal fees, insurance, interest and fees on construction loans, taxes incurred during construction, advertising and sales expense, and overhead and profit. Trended original costs shall be determined free on board (FOB) the mine site as of January 1, 2023.

Depreciation shall be determined by calculating the amount of physical deterioration using the lifetime depreciation method. Functional and economic obsolescence shall not be accounted for in the calculation of depreciation. No additional allowance shall be made for depreciation except as may be accounted for in the downtime allowance factor.

The downtime allowance and the downtime allowance factor for mine resource production equipment shall be determined by the schedule of rates method. The downtime allowance and the downtime allowance factor shall account for all the loss in value due to under-utilization of the resource production equipment. This includes any loss in value due to differences in replacement cost and difference in the amount of depreciation, that have not been taken into account using the procedures in this Manual.



Resource Production Equipment Subject: General Rules

#### **Replacement Cost New**

The following mine resource production equipment shall be valued:

- Head frame and head house including mechanical and electrical equipment;
- Service and production hoists c/w cages, skips, pulleys, cables, guide ropes and rails, skip load and dump facilities:
- Water control pipes, pumps, motors;
- Compressed air service piping, compressors, motors, controls;
- Personnel and service vehicles;
- Mobile and overhead cranes, forklifts;
- Ventilation systems, fans, ducts;
- Heating and cooling facilities;
- Warning system;
- Production equipment miners, drag lines, loaders, loading shovels, front-end loaders, ore trucks, ore haulers, scoop trams, conveyor systems and numerous ancillary and auxiliary equipment;
- Drills and blasting equipment;
- Feeders and crushers;
- Roof and floor maintenance equipment, rock bolters, graders, scraper haulers;
- Crawler and wheel tractors c/w dozers and/or buckets;
- Electrical wiring and equipment required to operate plant and equipment; and
- Any other equipment used in the mining operation that is not listed as an exclusion.

The following mine resource production equipment shall not be valued:

- Shaft linings concrete, steel, wood, etc. (tubing and cribbing);
- Safety equipment fire, personal, etc.;
- Sharp tools for maintenance and service;
- Spare parts; and
- Surplus equipment.

#### Unit-In-Place Method

The replacement cost of new conveyors and solution mining resource production equipment shall be determined as follows:

- 1. Determine the type of resource production equipment using the rating guide.
- 2. Determine the features requiring unit-in-place adjustment.
- 3. Calculate the replacement cost of the resource production equipment by adjusting the base rate by the unit-in-place adjustments.



Resource Production Equipment Subject: General Rules

### Trended Original Cost Method

The replacement cost new shall be determined as follows:

- 1. Determine the original construction cost of all the resource production equipment at the facility.
- 2. Determine the direct and indirect costs requiring an adjustment.
- 3. Determine the comparative cost index for mine resource production equipment required to adjust construction costs to January 1, 2023.
- 4. Calculate the construction cost of all the resource production equipment at the facility by adjusting the original construction cost for any direct or indirect costs requiring adjustment and multiplying the adjusted original construction cost by the comparative cost index.
- 5. Determine replacement cost of conveyors and solution mining resource production equipment that is valued by the unit-in-place method.
- 6. Calculate the replacement cost new of the resource production equipment by subtracting the replacement cost new of conveyors and solution mining resource production equipment from the construction cost of all the resource production equipment in the facility.

#### **Physical Deterioration**

#### Lifetime Depreciation Method

The amount of physical deterioration shall be 40 percent. When calculating replacement cost less depreciation no additional allowance shall be made for depreciation.

#### **Downtime Allowance**

#### Schedule of Rates Method

The downtime allowance for all mine resource production equipment shall be 10 percent.

#### **Downtime Allowance Factor**

### Schedule of Rates Method

The downtime allowance factor shall be determined for mine resource production equipment that is not used for 30 days or more in the 12 month period preceding January 1st of the year to which the assessment roll relates.

Periods of time less than 7 consecutive days during which mine resource production equipment is not used shall not be included in the calculation of the number of down days.

The downtime adjustment factor shall be determined by application of the following formula:

DAF = 
$$1 - \frac{DD - 30}{365}$$

where: DAF = downtime adjustment factor
DD = number of down days



Resource Production Equipment Subject: General Rules

# **Calculation Procedure**

Description	Document No.	Page No.
a) Conveyor Base Rate	4.2.3	1
b) Unit-in-Place Resource Production Equipment	4.2.1	2
c) Trended Original Cost Resource Production Equipment	4.2.1	3
d) Replacement Cost New = $(a + b + c)$		
e) RCN less Physical Deterioration and Downtime		
Allowance = $d x (1 - (e_1 + e_2))$		
e <sub>1</sub> . Physical Deterioration	4.2.1	3
e <sub>2</sub> . Downtime Allowance	4.2.1	3
f) Downtime Allowance Factor	4.2.1	3
g) Assessed Value (e x f)	_	



Resource Production Equipment Subject: Comparative Cost Factor

### **Description**

The comparative cost factors are used to determine the replacement cost new of mine resource production equipment valued by the trended original cost method.

#### **Application**

The trended original cost method shall be used when the individual components of resource production equipment cannot be determined or estimated. The trended original cost method shall not be used to determine the replacement cost of conveyors or solution mining resource production equipment.

## **Comparative Cost Factor**

The comparative cost factor shall be used to calculate the replacement cost new of resource production equipment as of January 1, 2023.

#### **Factors**

Year	Comparative Cost Factor
1940 and older	
1941	
1942	
1943	
1944	
1945	
1946	
1947	
1948	
1949	
1950	
1951	
1952	
1953	
1954	
1955	
1956	
1957	
1958	
1959	
1960	
1961	
1962	
1963	
1964	
1965	
1966	
1967	
1968	
1969	
1970	
1971	
1972	
1973	
1974	

Portions of this section are not available for viewing due to licensing with Marshall and Swift, published by CoreLogic Inc. Therefore the factors etc. have been intentionally left blank.

This information is available for purchase by contacting:

Technical Standards and Policy Division
Saskatchewan Assessment Management Agency
200 – 2201 – 11<sup>th</sup> Avenue
Regina, Saskatchewan S4P 0J8

Phone: (306) 924-8000 Toll Free: 1-800-667-SAMA (7262) Fax: (306) 924-8070

Email: <u>info.request@sama.sk.ca</u>

Website: http://www.sama.sk.ca



Resource Production Equipment Subject: Comparative Cost Factor

Year	Comparative Cost Factor
1975	comparative cost ractor
1976	
1977	
1978	
1979	
1980	
1981 1982	
1983	
1984	
1985	
1986	
1987	
1988	
1989	
1990	
1991	
1992	
1993	
1994	
1995	
1996	
1997	
1998	
1999	
2000	
2001	
2002	
2003	
2004	
2005	
2006	
2007	
2008	
2009	
2010	
2011	
2012	
2013	
2014	
2015	
2016	
2017	
2018	
2019	
2020	
2021	
2022 and newer	
2022 and newel	

This table is a derivative work based on the "Marshall & Swift Valuation Service" which is the copyrighted material of Marshall & Swift, published by CoreLogic Inc. © 2022. Unauthorized reproduction is expressly prohibited.



Resource Production Equipment Subject: Conveyors

# Description

Conveyors are used to transport ore within a mine facility.


## **Application**

The rate schedule shall be applied to continuous belt conveyors over 1,000 feet in length. Continuous belt conveyors less that 1,000 feet in length and all special design, tripper automatic loading and unloading, extensible, mobile bridge and bridge conveyors shall be valued by the trended original cost method.

## **Continuous Belt Conveyor**

The rates for conveyors are in dollars per lineal foot.

Belt Width (in.)	Rate
24	337
30	396
36	462
42	498
48	621
54	698
60	747
72	888
Rates include:	
- belting	
- drives	
- structure	
- hardware	





Resource Production Equipment Subject: Conveyors